

AWP20

Large Shallow Wall Pack

Housing: Die-cast aluminum housing and hinged front frame, 1/2" coin plugs with O-rings for conduit and photocell, textured architectural bronze powdercoat finish over a chromate conversion coating

Reflector: Aluminum reflector

Lens: Molded prismatic borosilicate glass lens

Socket: Porcelain 5KV pulse rated mogul base socket with nickel-plated screw shell

Mounting: Cast-in template for mounting directly over a 4" recessed outlet box, or use 1/2" surface conduit.

Wattage: High Pressure Sodium: 100 to 250w
Pulse-start / Metal Halide: 100 to 250w
LED: 2 x 7.5w, 3 x 7.5w, 2 x 15w, 3 x 15w

Listings & Ratings: CSA Listed for wet locations



Catalog #	Wattage	Voltage	Lamp	Ballast
AWP20H100QMG	100	Quad	HPS	HX-HPF
AWP20H150QMG	150	Quad	HPS	HX-HPF
AWP20H250Q	250	Quad	HPS	CWA
AWP20M100QMG	100	Quad	MH	HX-HPF
AWP20M150Q	150	Quad	MH	HX-HPF
AWP20P250Q	250	Quad	PS \oplus	CWA
AWP20L2X7HQ	2 x 7.5	120-277	LED	Electronic
AWP20L3X7HQ	3 x 7.5	120-277	LED	Electronic
AWP20L2X15Q	2 x 15	120-277	LED	Electronic
AWP20L3X15Q	3 x 15	120-277	LED	Electronic

Items marked with \oplus meet EISA regulations for 150-500 watt Metal Halide luminaires.

Dimensions	Photometrics
<p>AWP20</p>	<p>AWP20PS250</p> <p>Percent Lamp Lumens: Front: Low=7.2%, Medium=12.2%, High=5.6%, Very High=2.8% Back: Low=4.7%, Medium=5.1%, High=1.5%, Very High=0.2% Light Loss Coef: 0%, High=0.2% BUG Rating: B3-U4-G4</p>

Options and Accessories	
Catalog #	Description
PC1	120V Photocell (Field Installed)
PC2	208-277V Photocell (Field Installed)
QRS	Quartz Restrike Module (supplied with 100w DC bayonet base lamp)
WP25FC	Full cutoff, stamped steel, textured bronze finish
WP25LG	Clear polycarbonate vandal resistant guard
WP25SC	Side cutoff, stamped steel, textured bronze finish
WP25WG	Wire guard, stainless steel construction

<p>PC1 / PC2</p>	<p>QRS</p>	<p>WP25FC (shown mounted)</p>
<p>WP25LG (shown mounted)</p>	<p>WP25SC (shown mounted)</p>	<p>WP25WG (shown mounted)</p>

Specifications subject to change without notice.