



**Cylinder 260 STEMT** H: 8.88 W: 4.5 OAL: 22.75

**Description**

4.5" Square cylinder, suspended by 12" stem with 40° swivel canopy  
 Designed for use with uni-directional LED or reflector type (R/PAR) lamps

**Specifications**

- Housing** Extruded aluminum cylinder with stamped steel canopy
- Diffuser/Optics** Clear tempered glass bottom lens
- Light Source** MBL Medium Base
- Max Watts** 25 75
- Electrical**
  - MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
  - MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



**Ordering Guide:** Choose from each category, using designated code to specify.

|           |          |              |        |        |
|-----------|----------|--------------|--------|--------|
| 260 STEMT |          |              |        |        |
| MODEL     | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |

**Diffuser/Optics**

Clear tempered glass

**Light Source**

- MBL13 PAR FL - 13W/30K 1000 Lm PAR30
- MBL13 PAR SP - 13W/30K 1000 Lm PAR30
- MBL13 PAR WFL - 13W/30K 1000 Lm PAR30
- MB25 PAR - 25W MAX. MED base (Par30 lamp by others)
- MB - Maximum 75W Par30 (by others)

**Finish**

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded\***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium\***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**

- SSP 120 4KV 120V MOV1 Surge Suppressor