



Cylinder 261 CMX H: 11.5 W: 6

Description

6" Square, surface-mounted cylinder
Designed for use with LED light engines

Specifications

| | |
|------------------------|---|
| Housing | Extruded aluminum cylinder with extended canopy (not shown)* |
| Diffuser/Optics | • Bare lamp (open aperture) • Reflector |
| Light Source | LED |
| Max Watts | 11.3 |
| Electrical | TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent). |
| Mounting | Mounts over 4" recessed outlet box. |
| Certification | Manufactured in accordance with U.L. standard 1598 - For dry locations only |

Ordering Guide: Choose from each category, using designated code to specify.

| | | | | |
|---------|----------|--------------|--------|--------|
| 261 CMX | | | | |
| MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |

Diffuser/Optics

- Bare-lamp (open aperture)
- R - Flood Reflector

Light Source

- TL5 HO - 4.59W/40K 1287 Lm, 120V dimmable
- TL5 - 4.7W/30K 909 Lm, 120V dimmable
- TL6 HO - 6.16W/40K 1588 Lm, 120V dimmable
- TL6 - 6.32W/30K 1208 Lm, 120V dimmable
- TL8 HO - 7.75W/40K 1886 Lm, 120V dimmable
- TL8 - 7.96W/30K 1502 Lm, 120V dimmable
- TL9 HO - 9.36W/40K 2179 Lm, 120V dimmable
- TL10 - 9.62W/30K 1790 Lm, 120V dimmable
- TL11 HO - 10.99W/40K 2470 Lm, 120V dimmable
- TL11 - 11.3W/30K 2075 Lm, 120V dimmable

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - [Specify Color #](#)
- UPG - [Select Color from Luraline Palette](#)
- Premium***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K Non-Stock item - consult factory for availability
- 35K Neutral White
- DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP 10KV 120-277V Supplemental Surge Protection

NOTES:
*Driver is housed in extended aluminum canopy (not shown)