



Cylinder 261 WM H: 9.75 W: 6 E: 9.3 MC: 3.875

Description

6" Square Downlight cylinder wall-mount

Specifications

Housing	Designed for use with uni-directional LED or reflector type (R/PAR) lamps	
Diffuser/Optics	Bare lamp (open aperture)	
Light Source	MBL	Medium Base
Max Watts	25	120
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.	
Mounting	Mounts over 4" recessed outlet box.	
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations	



Ordering Guide: Choose from each category, using designated code to specify.

261 WM				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- Bare-lamp (open aperture)

Light Source

MBL15 PAR SP - 15W/30K 1200 Lm PAR38
MBL15 PAR WFL - 15W/30K 1200 Lm PAR38
MBL15 PAR FL - 15W/30K 1200 Lm PAR38
MBL18 PAR FL - 18W/30K 1400 Lm PAR38
MB25 PAR - 25W MAX. MED base (Par38 lamp by others)
MB - Maximum 120W Par38 (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from [Luraline Palette](#)
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

SSP 10KV 120-277V Supplemental Surge Protection