



Legacy Product 278 CM H: 7 W: 4.50

Description

MOQ may apply - please consult factory.
4.5" Diameter, surface-mounted cylinder
Designed for use with uni-directional LED or reflector type (R/PAR) lamps

Specifications

Housing	Spun aluminum cylinder	
Diffuser/Optics	<ul style="list-style-type: none"> • Bare lamp (open aperture) • Clear tempered glass bottom lens 	
Light Source	MBL	Medium Base
Max Watts	25	75
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.	
Mounting	Mounts over 4" recessed outlet box.	
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only	

Ordering Guide: Choose from each category, using designated code to specify.

278 CM					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

- Bare-lamp (open aperture)
T78 - Clear tempered glass

Light Source

MBL9.8A - 9.8W/30K 800 Lm OmniLED
MBL13 PAR FL - 13W/30K 1000 Lm PAR30
MBL13 PAR SP - 13W/30K 1000 Lm PAR30
MBL13 PAR WFL - 13W/30K 1000 Lm PAR30
MB25 PAR - 25W MAX. MED base (Par30 lamp by others)
MB - Maximum 75W Par30 (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)