



Cylinder 278 CORD H: 7.56 W: 4.5 OAL: 44.5

Description

4.5" Diameter cylinder pendant, 36" cord-hung with Black 18-3 cord. (White cord supplied with white fixtures)
Designed for use with uni-directional LED or reflector type (R/PAR) lamps

Specifications

Housing	Spun aluminum cylinder	
Diffuser/Optics	Bare lamp (open aperture)	
Light Source	MBL	Medium Base
Max Watts	25	75
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.	
Mounting	Mounts over 4" Recessed Outlet Box	
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only	



Ordering Guide: Choose from each category, using designated code to specify.

278 CORD				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Bare-lamp

Light Source

- MBL13 PAR FL** - 13W/30K 1000 Lm PAR30
- MBL13 PAR SP** - 13W/30K 1000 Lm PAR30
- MBL13 PAR WFL** - 13W/30K 1000 Lm PAR30
- MB25 PAR** - 25W MAX. MED base (Par30 lamp by others)
- MB** - Maximum 75W Par30 (by others)

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- SSP 120** 4KV 120V MOV1 Surge Suppressor