



Cylinder 279 CMT H: 9 W: 6

Description

6" Diameter, surface-mounted cylinder
Designed for use with uni-directional LED or reflector type (R/PAR) lamps

Specifications

Housing	Spun aluminum cylinder	
Diffuser/Optics	Clear tempered glass bottom lens	
Light Source	MBL	Medium Base
Max Watts	25	120
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.	
Mounting	Mounts over 4" recessed outlet box.	
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations	



Ordering Guide: Choose from each category, using designated code to specify.

279 CMT				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Clear tempered glass

Light Source

- MBL9.8A** - 9.8W/30K 800 Lm OmniLED
- MBL15 PAR SP** - 15W/30K 1200 Lm PAR38
- MBL15 PAR WFL** - 15W/30K 1200 Lm PAR38
- MBL15 PAR FL** - 15W/30K 1200 Lm PAR38
- MBL18 PAR FL** - 18W/30K 1400 Lm PAR38
- MB25 PAR** - 25W MAX. MED base (Par38 lamp by others)
- MB** - Maximum 120W Par38 (by others)

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- B79** Black milli-groove baffle (Not Available with Tempered glass lens)
- SSP 120** 4KV 120V MOV1 Surge Suppressor