



Cylinder 288 STEM H: 12.88 W: 8 OAL: 27.75

Description

8" Square cylinder, suspended by 12" stem with 40° swivel canopy
 Designed for use with uni-directional LED or reflector type (R/PAR) lamps

Specifications

- Housing** Extruded aluminum cylinder with stamped steel canopy
- Diffuser/Optics** Bare lamp (open aperture) - For LENSED aperture, see Model No. 288 WMXT
- Light Source** MBL Medium Base
- Max Watts** 25 120
- Electrical**
 - MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
 - MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only



Ordering Guide: Choose from each category, using designated code to specify.

288 STEM					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

- Bare-lamp (open aperture)

Light Source

- MBL15 PAR FL** - 15W/30K 1200 Lm PAR38
- MBL15 PAR SP** - 15W/30K 1200 Lm PAR38
- MBL15 PAR WFL** - 15W/30K 1200 Lm PAR38
- MBL18 PAR FL** - 18W/30K 1400 Lm PAR38
- MB25 PAR** - 25W MAX. MED base (Par38 lamp by others)
- MB** - Maximum 120W Par38 (by others)

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

SSP 120 4KV 120V MOV1 Surge Suppressor