



**Cylinder 288 UD** H: 19 W: 8 E: 12.25 MC: 9.5

**Description**

8" Square Up/Down cylinder wall-mount  
Designed for use with uni-directional LED or reflector type (R/PAR) lamps

**Specifications**

- Housing** Fabricated aluminum cylinder with die-cast arm/back
- Diffuser/Optics** Bare lamp (open aperture) - For LENSED aperture, see Model No. 288 WMXT
- Light Source** MBL Medium Base
- Max Watts** 18 X 2 250 X 2
- Electrical** MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.  
MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only



**Ordering Guide:** Choose from each category, using designated code to specify.

288 UD				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

- Bare-lamp (open aperture)

**Light Source**

- 2MBL15 PAR FL** - 30W/30K 2400 Lm PAR38
- 2MBL15 PAR SP** - 30W/30K 2400 Lm PAR38
- 2MBL15 PAR WFL** - 30W/30K 2400 Lm PAR38
- 2MBL18 PAR FL** - 36W/30K 2800 Lm PAR38
- MB** - Maximum 2x 250W Par38
- Bare-lamp model only

**Finish**

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**