



Decorative 716 CORDX H: 16 W: 16 OAL: 54.50

Description

16" Globe pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

Specifications

- Housing** Stamped steel slip fitter and canopy
- Diffuser/Optics** WACS - Seamless White Acrylic
- Light Source** LED
- Max Watts** 15.94
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only

Ordering Guide: Choose from each category, using designated code to specify.



Diffuser/Optics

WACS - 1-piece White Acrylic (blow-molded)

Light Source

- TL8** - 7.96W/30K 1502 Lm, 120V dimmable
- TL9 HO** - 9.36W/40K 2179 Lm, 120V dimmable
- TL10** - 9.62W/30K 1790 Lm, 120V dimmable
- TL11 HO** - 10.99W/40K 2470 Lm, 120V dimmable
- TL11** - 11.3W/30K 2075 Lm, 120V dimmable
- TL13 HO** - 12.62W/40K 2756 Lm, 120V dimmable
- TL13** - 12.99W/30K 2352 Lm, 120V dimmable
- TL14 HO** - 14.28W/40K 3040 Lm, 120V dimmable
- TL15** - 14.69W/30K 2626 Lm, 120V dimmable
- TL16 HO** - 15.94W/40K 3320 Lm, 120V dimmable

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from [Luraline Palette](#)
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 35K** Neutral White
- 40K**
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- OSC 6**
- SSP** 10KV 120-277V Supplemental Surge Protection

NOTES: When illuminated by certain light sources, a "shadow" may be visible at the bottom of Seamless White Acrylic globes (WACS). This is a result of the rotational molding process, NOT a manufacturing defect. While 2-piece (WAC2) are shadowless, the buffed seam is slightly visible.