



Decorative 724 STEM H: 24 W: 24 OAL: 37.75

Description

24" Globe pendant with 12" stem and 40° swivel canopy

Specifications

Housing Spun aluminum fitter and stamped steel canopy

Diffuser/Optics WAC2 - 2-pc. White Acrylic

Light Source Medium Base

Max Watts 300

Electrical
MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.
GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.

Mounting Mounts over 4" recessed outlet box.

Certification Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



Ordering Guide: Choose from each category, using designated code to specify.

724 STEM					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

WAC2 - 2-piece White Acrylic (fabricated w/polished seam)

Light Source

MB25 A - 25W MAX. MED base (A19 lamp by others)
MB - Maximum 300W PS (by others)

Finish

Standard
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

SSP 120 4KV 120V MOV1 Surge Suppressor

NOTES: 2-piece White acrylic (WAC2) globes have a slightly visible buffed seam.
 2-piece White acrylic (WAC2) globes have a slightly visible buffed seam.
 2-piece White acrylic (WAC2) globes have a slightly visible buffed seam.
 2-piece White acrylic (WAC2) globes have a slightly visible buffed seam.
 2-piece White acrylic (WAC2) globes have a slightly visible buffed seam.
 2-piece White acrylic (WAC2) globes have a slightly visible buffed seam.
 2-piece White acrylic (WAC2) globes have a slightly visible buffed seam.
 2-piece White acrylic (WAC2) globes have a slightly visible buffed seam.
 2-piece White acrylic (WAC2) globes have a slightly visible buffed seam.