



**Decorative 730 STEM** H: 30 W: 30 OAL: 43.75

**Description**

30" Globe pendant with 12" stem and 40° swivel canopy

**Specifications**

**Housing** Spun aluminum fitter and stamped steel canopy

**Diffuser/Optics** WAC2 - 2-pc. White Acrylic

**Light Source** GUL MBL Medium Base

**Max Watts** 15 15 300

**Electrical**  
**MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.  
**MBL** - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.  
**GUL** - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.

**Mounting** Mounts over 4" recessed outlet box.

**Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only



**Ordering Guide:** Choose from each category, using designated code to specify.

730 STEM					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

**WAC2** - 2-piece White Acrylic (fabricated w/polished seam)

**Light Source**

**MB25 A** - 25W MAX. MED base (A19 lamp by others)  
**GUL11A** - 11W/27K 1100 Lm GU24 OmniLED  
**MBL11A** - 11W/30K 1100 Lm OmniLED  
**MBL15A** - 15./30K 1600 Lm OmniLED  
**GUL15A** - 15W/27K 1600 Lm GU24 OmniLED  
**MB** - Maximum 300W PS (by others)

**Finish**

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from Luraline Palette

**Extras (Order Separately)**

**SSP 120** 4KV 120V MOV1 Surge Suppressor

**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

NOTES: 2-piece White acrylic (WAC2) globes have a slightly visible buffed seam.  
 2-piece White acrylic (WAC2) globes have a slightly visible buffed seam.  
 2-piece White acrylic (WAC2) globes have a slightly visible buffed seam.  
 2-piece White acrylic (WAC2) globes have a slightly visible buffed seam.