



Decorative 736 STEMX H: 36 W: 36 OAL: 51.50

Description

36" Globe pendant with 12" stem and 40° swivel canopy

Specifications

<p>Housing Mounting Certification</p>	<p>Spun aluminum fitter and stamped steel canopy* Mounts over 4" recessed outlet box. Manufactured in accordance with U.L. standard 1598 - For dry locations only</p>
---	---

Ordering Guide: Choose from each category, using designated code to specify.

736 STEMX					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser / Optics

Light Source

Finish

Extras (Order Separately)

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- 50K** Daylight (Non-Stock item - consult factory for availability)
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection

NOTES: 2-piece White acrylic (WAC2) globes have a slightly visible buffed seam.

*Driver is housed in extended aluminum canopy (not shown)