



Decorative ABC30HB H: 9 W: 30 OAL: 35.50

Description

Cable-hung 30" Acrylic Bowl pendant with half-ball trim

Specifications

Housing Mixed metals

Light Source GUL LTE Medium Base

Max Watts 15.5 X 4 11.4 X 4 150 X 4

Electrical MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
 MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.
 DOB - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board.
 QE/TE - Includes 4-pin CF lamp with 120-277V HPF electronic ballast

Mounting Mounts over 4" recessed outlet box.

Certification Manufactured in accordance with U.L. standard 1598 - For dry locations only



Ordering Guide: Choose from each category, using designated code to specify.

ABC30HB				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Light Source

4L11 LTE - 45.6W/30K 6520 Lm LED
4GUL15.5 A21 - 62W/27K 6400 Lm GU24 OmniLED
MB - Maximum 4x150W A (by others)

Finish

Standard Upgraded*
RAL - [Specify Color #](#)
UPG - Select Color from [Luraline Palette](#)
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

SSP 120 4KV 120V MOV1 Surge Suppressor