


Project:

Fixture Type:





Decorative ABC36HB

Description

Cable-hung 36" Acrylic Bowl pendant with half-ball trim

Specifications

Housing Mixed metals

Light Source LTE Medium Base

Max Watts 11.4 X 6 150 X 6

Electrical - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.

> - Includes 50,000 Hr. LED light engine with 120-277V constant current driver. LTE

H: 11 W: 36 OAL: 35

Mounting Mounts over 4" recessed outlet box.

Certification Manufactured in accordance with U.L. standard 1598 - For dry locations only



| raering Guide: | Choose from | each | category, | using | designated | code t | :o specif | у. |
|----------------|-------------|------|-----------|-------|------------|--------|-----------|----|
|----------------|-------------|------|-----------|-------|------------|--------|-----------|----|

ABC36HB

MODEL **DIFFUSER** LIGHT SOURCE **FINISH EXTRAS**

Diffuser/Optics **Light Source**

6L7 LTE - 43.2W/30K 6810 lumen LED 120-277V HPF

6L11 LTE - 68.4W/30K 9780 lumen LED

MB - Maximum 6x 150W A

(by others)

Finish

Standard

Upgraded*

RAL - Specify Color # $\boldsymbol{\mathsf{UPG}}$ - Select Color from

Luraline Pallette

Premium*

CCM - Custom Color CIC - Inner Color CTC - Clear Top Coat * Subject to Surcharge SSP 120 4KV 120V MOV1 Surge Suppressor

Extras (Order Separately)

