



ABR30* shown



Decorative ABR24HB H: 8 W: 24 OAL: 36

Description

Rod-hung 24" Acrylic Bowl pendant with half-ball trim

Specifications

Housing	Mixed metals					
Diffuser/Optics	<ul style="list-style-type: none"> FAL - Faux-Alabaster Acrylic SOA - Satin Opal Acrylic WAC - White Acrylic 					
Light Source	GUL	LTE	MBL	Medium Base	LTE	LTE
Max Watts	15.5 X 3	11.4 X 3	15.5 X 3	150 X 3	11.4 X 4	11.4 X 6
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures. DOB - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board. QE/TE - Includes 4-pin CF lamp with 120-277V HPF electronic ballast					
Mounting	Mounts over 4" recessed outlet box.					
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only					



Ordering Guide: Choose from each category, using designated code to specify.

ABR24HB					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

- FAL** - Faux-Alabaster Acrylic
- SOA** - Satin Opal Acrylic
- WAC** - White Acrylic

Light Source

- 3L11 LTE** - 34.2W/30K 4890 Lm LED
- 6L11 LTE** - 68.4W/30K 9780 lumen LED
- 4L11 LTE** - 45.6W/30K 6520 Lm LED
- 3GUL15.5 A21** - 46.5W/27K 4800 Lm GU24 OmniLED
- 3MBL15.5 A21** - 46.5W/30K 4950 Lm OmniLED
- MB** - Maximum 3x 150W A (by others)

Finish

- Standard Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from [Luraline Palette](#)
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- SSP 120** 4KV 120V MOV1 Surge Suppressor