




ABR30<sup>+</sup>  
shown



## Decorative ABR36HB H: 11 W: 36 OAL: 35

### Description

Rod-hung 36" Acrylic Bowl pendant with half-ball trim

### Specifications

<b>Housing</b>	Mixed metals	
<b>Diffuser/Optics</b>	<ul style="list-style-type: none"> <li>• FAL - Faux-Alabaster Acrylic</li> <li>• SOA - Satin Opal Acrylic</li> <li>• WAC - White Acrylic</li> </ul>	
<b>Light Source</b>	LTE	Medium Base
<b>Max Watts</b>	11.4 X 6	150 X 6
<b>Electrical</b>	<b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. <b>LTE</b> - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.	
<b>Mounting</b>	Mounts over 4" recessed outlet box.	
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - For dry locations only	



### Ordering Guide: Choose from each category, using designated code to specify.

ABR36HB					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

#### Diffuser/Optics

**FAL** - Faux-Alabaster Acrylic  
**SOA** - Satin Opal Acrylic  
**WAC** - White Acrylic

#### Light Source

**6L7 LTE** - 43.2W/30K 6810 lumen LED 120-277V HPF  
**6L11 LTE** - 68.4W/30K 9780 lumen LED  
**MB** - Maximum 6x 150W A (by others)

#### Finish

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from [Luraline Palette](#)  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

#### Extras (Order Separately)

**2DIM010** LED 4-wire 0-10V Dimming - 120-277V  
**BBL** 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)  
**SSP** 10KV 120-277V Supplemental Surge Protection