



Decorative ABS24 H: 8 W: 24 OAL: 36

Description

Stem-hung 24" Acrylic Bowl pendant

Specifications

Housing	Mixed metals				
Diffuser/Optics	<ul style="list-style-type: none"> • FAL - Faux-Alabaster Acrylic • Satin Opal Acrylic • White Acrylic 				
Light Source	GUL	LTE	MBL	Medium Base	LTE
Max Watts	15.5 X 3	11.4 X 3	15.5 X 3	150 X 3	11.4 X 6
Electrical	<p>MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.</p> <p>MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.</p> <p>LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.</p>				
Mounting	Mounts over 4" recessed outlet box.				
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only				



Ordering Guide: Choose from each category, using designated code to specify.

ABS24					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

FAL - Faux-Alabaster Acrylic
SOA - Satin Opal Acrylic
WAC - White Acrylic

Light Source

3L11 LTE - 34.2W/30K 4890 Lm LED
6L11 LTE - 68.4W/30K 9780 lumen LED
3GUL15.5 A21 - 46.5W/27K 4800 Lm GU24 OmniLED
3MBL15.5 A21 - 46.5W/30K 4950 Lm OmniLED
MB - Maximum 3x 150W A (by others)

Finish

Standard
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from [Luraline Palette](#)
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

27K Non-Stock item - consult factory for availability
35K Neutral White
BBL 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)
DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
SSP 10KV 120-277V Supplemental Surge Protection