



**Decorative ABS24HB** H: 8 W: 24 OAL: 36

**Description**

Stem-hung 24" Acrylic Bowl pendant with half-ball trim

**Specifications**

|                        |  |          |          |             |          |          |
|------------------------|--|----------|----------|-------------|----------|----------|
| <b>Housing</b>         | Mixed metals   |          |          |             |          |          |
| <b>Diffuser/Optics</b> | <ul style="list-style-type: none"> <li>• FAL - Faux-Alabaster Acrylic</li> <li>• SOA - Satin Opal Acrylic</li> <li>• WAC - White Acrylic</li> </ul>  |          |          |             |          |          |
| <b>Light Source</b>    | GUL  | LTE      | MBL      | Medium Base | LTE      | LTE      |
| <b>Max Watts</b>       | 15.5 X 3   | 11.4 X 3 | 15.5 X 3 | 150 X 3     | 11.4 X 4 | 11.4 X 6 |
| <b>Electrical</b>      | <p><b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.</p> <p><b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.</p> <p><b>DOB</b> - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board.</p> <p><b>QE/TE</b> - Includes 4-pin CF lamp with 120-277V HPF electronic ballast</p> |          |          |             |          |          |
| <b>Mounting</b>        | Mounts over 4" recessed outlet box.  |          |          |             |          |          |
| <b>Certification</b>   | Manufactured in accordance with U.L. standard 1598 - For dry locations only  |          |          |             |          |          |



**Ordering Guide:** Choose from each category, using designated code to specify.

|         |          |              |        |        |  |
|---------|----------|--------------|--------|--------|--|
| ABS24HB |          |              |        |        |  |
| MODEL   | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |  |

**Diffuser/Optics**

- FAL** - Faux-Alabaster Acrylic
- SOA** - Satin Opal Acrylic
- WAC** - White Acrylic

**Light Source**

- 3L11 LTE** - 34.2W/30K 4890 Lm LED
- 6L11 LTE** - 68.4W/30K 9780 lumen LED
- 4L11 LTE** - 45.6W/30K 6520 Lm LED
- 3GUL15.5 A21** - 46.5W/27K 4800 Lm GU24 OmniLED
- 3MBL15.5 A21** - 46.5W/30K 4950 Lm OmniLED
- MB** - Maximum 3x 150W A (by others)

**Finish**

- Standard Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from [Luraline Palette](#)
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**

- SSP 120** 4KV 120V MOV1 Surge Suppressor