



Decorative ABS30 H: 9 W: 30 OAL: 35.50

Description

Stem-hung 30" Acrylic Bowl pendant

Specifications

Housing	Mixed metals		
Diffuser/Optics	<ul style="list-style-type: none"> • FAL - Faux-Alabaster Acrylic • SOA - Satin Opal Acrylic • WAC - White Acrylic 		
Light Source	GUL	LTE	Medium Base
Max Watts	15.5 X 4	11.4 X 4	150 X 4
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver. LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.		
Mounting	Mounts over 4" recessed outlet box.		
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only		



Ordering Guide: Choose from each category, using designated code to specify.

ABS30					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

FAL - Faux-Alabaster Acrylic
SOA - Satin Opal Acrylic
WAC - White Acrylic

Light Source

4L11 LTE - 45.6W/30K 6520 Lm LED
4GUL15.5 A21 - 62W/27K 6400 Lm GU24 OmniLED
MB - Maximum 4x150W A (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

SSP 120 4KV 120V MOV1 Surge Suppressor