



Decorative ABS36 H: 11 W: 36 OAL: 35

Description

Stem-hung 36" Acrylic Bowl pendant

Specifications

- Housing** Mixed metals
- Diffuser/Optics**
- FAL - Faux-Alabaster Acrylic
 - SOA - Satin Opal Acrylic
 - WAC - White Acrylic
- Light Source** LTE Medium Base
- Max Watts** 7.2 X 6 150 X 6
- Electrical**
- MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
 - MBL** - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.
 - DOB** - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board.
 - QE/TE** - Includes 4-pin CF lamp with 120-277V HPF electronic ballast
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only



Ordering Guide: Choose from each category, using designated code to specify.

ABS36					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

FAL - Faux-Alabaster Acrylic
SOA - Satin Opal Acrylic
WAC - White Acrylic

Light Source

6L7 LTE - 43.2W/30K 6810 lumen LED 120-277V HPF
MB - Maximum 6x 150W A (by others)

Finish

Standard
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

SSP 120 4KV 120V MOV1 Surge Suppressor