



**Canopy AVN30** H: 7 1/4 W: 9

**Description**

Medium Vandal Resistant Light - Deep Housing

**Specifications**

Housing	Die-cast aluminum		
Diffuser	Clear Polycarbonate		
Light Source	Fluorescent	HID	LED
Max Watts	42	50	22.5
Electrical	HID - Includes Pulse-start metal halide lamp with 120/277V HPF magnetic ballast		
Mounting	Mounts over 4" recessed outlet box or surface conduit		
Certification			

**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide	AVN30				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser**  
Clear Polycarbonate Lens

**Light Source**  
**L23 LTE 50K** - 22.5W/50K 3270 lumen LED  
**F26 TE** - 26W/30K 1800 lumen CF  
**F32 TE** - 32W/30K 2400 lumen CF  
**F42 TE** - 42W/30K 3200 lumen CF  
**M50 DT** - 50W PSMH 120/277V HPF

**Finish**  
**Standard**  
**ZT** - Bronze

**Extras (Order Separately)**  
**PC1** Field installed 120V PHOTOCELL  
**PC2** Field installed 277V PHOTOCELL  
**TPS** Tamper-proof Screw