



**Canopy AVN30** H: 7 1/4 W: 9

**Description**

Medium Vandal Resistant Light - Deep Housing

**Specifications**

**Housing** Die-cast aluminum

**Diffuser/Optics** Clear Polycarbonate

<b>Light Source</b>	Fluorescent	HID	LED
<b>Max Watts</b>	42	50	22.5

**Electrical Mounting** HID - Includes Pulse-start metal halide lamp with 120/277V HPF magnetic ballast  
Mounts over 4" recessed outlet box or surface conduit

**Certification**

**Ordering Guide:** Choose from each category, using designated code to specify.

AVN30					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

Clear Polycarbonate Lens

**Light Source**

**L23 LTE 50K** - 22.5W/50K 3270 lumen LED  
**F26 TE** - 26W/30K 1800 lumen CF  
**F32 TE** - 32W/30K 2400 lumen CF  
**F42 TE** - 42W/30K 3200 lumen CF  
**M50 DT** - 50W PSMH 120/277V HPF

**Finish**

**Standard**  
**ZT** - Bronze

**Extras (Order Separately)**

**PC1** Field installed 120V PHOTOCELL  
**PC2** Field installed 277V PHOTOCELL  
**TPS** Tamper-proof Screw