



Canopy AVN30 H: 7 1/4 W: 9

Description

Medium Vandal Resistant Light - Deep Housing

Specifications

Housing	Die-cast aluminum		
Diffuser/Optics	Clear Polycarbonate		
Light Source	Fluorescent	HID	LED
Max Watts	42	50	22.5
Electrical Mounting	HID - Includes Pulse-start metal halide lamp with 120/277V HPF magnetic ballast Mounts over 4" recessed outlet box or surface conduit		
Certification			

Ordering Information

Choose one from each category, filling in the guide using designated code.

Guide	<u>AVN30</u>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Clear Polycarbonate Lens

Light Source

L23 LTE 50K - 22.5W/50K 3270 lumen LED
F26 TE - 26W/30K 1800 lumen CF
F32 TE - 32W/30K 2400 lumen CF
F42 TE - 42W/30K 3200 lumen CF
M50 DT - 50W PSMH 120/277V HPF

Finish

Standard
ZT - Bronze

Extras (Order Separately)

PC1 Field installed 120V PHOTOCELL
PC2 Field installed 277V PHOTOCELL
TPS Tamper-proof Screw