


L45 LTE 50K Light Source



Canopy AVN40 H: 8 5/8 W: 12 3/8

Description

Large Vandal Resistant Light - Deep Housing

Specifications

Housing Die-cast aluminum

Diffuser/Optics Clear Polycarbonate

Light Source LTE

Max Watts 45

Electrical TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).

Mounting Mounts over 4" recessed outlet box or surface conduit

Certification



Ordering Guide: Choose from each category, using designated code to specify.

AVN40				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Clear Polycarbonate Lens

Light Source

L45 LTE 50K - 45.4W/50K 6340 lumen LED

Finish

Standard
ZT - Bronze

Extras (Order Separately)

(D) FUSE DOUBLE FUSED
(S) FUSE SINGLE FUSED
BBL 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)
DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
PC1 Field installed 120V PHOTOCELL
PC2 Field installed 277V PHOTOCELL
SSP 10KV 120-277V Supplemental Surge Protection