



**Wall Pack AWP13** H: 13 W: 7.75 E: 5.50

**Description**

Mini die cast Wall Pack supplied with fully gasketted borosilicate glass diffuser

**Specifications**

Housing	Die-cast aluminum			
Diffuser/Optics	Prismatic Borosilicate glass			
Light Source	Fluorescent	HID	LED	Fluorescent
Max Watts	42	50	18.6	42 X 2
Electrical	HID - Includes Pulse-start metal halide lamp with 120/277V HPF magnetic ballast			
Mounting	Mounts over 4" recessed outlet box or via surface conduit			
Certification				

**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide	<u>AWP13</u>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

Clear Prismatic Borosilicate glass

**Light Source**

- L19 LTE 50K** - 18.6W/50K 2610 lumen LED
- 2F26 TE** - 52W/30K 3600 lumen CF
- F26 TE** - 26W/30K 1800 lumen CF
- F32 TE** - 32W/30K 2400 lumen CF
- 2F32 TE** - 64W/30K 4800 lumen CF
- 2F42 TE** - 84W/30K 6400 lumen CF
- F42 TE** - 42W/30K 3200 lumen CF
- M50 DT** - 50W PSMH 120/277V HPF

**Finish**

- Standard**
- ZT** - Bronze

**Extras (Order Separately)**

- BBE** Battery Backup - For Compact Fluorescent only (specify 120V Or 277V)
- PC1** Field installed 120V PHOTOCELL
- PC2** Field installed 277V PHOTOCELL