



Wall Pack AWP13 H: 13 W: 7.75 E: 5.50

Description

Mini die cast Wall Pack supplied with fully gasketted borosilicate glass diffuser

Specifications

Housing	Die-cast aluminum			
Diffuser/Optics	Prismatic Borosilicate glass			
Light Source	Fluorescent	HID	LED	Fluorescent
Max Watts	42	50	18.6	42 X 2
Electrical	HID - Includes Pulse-start metal halide lamp with 120/277V HPF magnetic ballast			
Mounting	Mounts over 4" recessed outlet box or via surface conduit			
Certification				

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	<u>AWP13</u>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Clear Prismatic Borosilicate glass

Light Source

- L19 LTE 50K** - 18.6W/50K 2610 lumen LED
- 2F26 TE** - 52W/30K 3600 lumen CF
- F26 TE** - 26W/30K 1800 lumen CF
- F32 TE** - 32W/30K 2400 lumen CF
- 2F32 TE** - 64W/30K 4800 lumen CF
- 2F42 TE** - 84W/30K 6400 lumen CF
- F42 TE** - 42W/30K 3200 lumen CF
- M50 DT** - 50W PSMH 120/277V HPF

Finish

- Standard**
- ZT** - Bronze

Extras (Order Separately)

- BBE** Battery Backup - For Compact Fluorescent only (specify 120V Or 277V)
- PC1** Field installed 120V PHOTOCELL
- PC2** Field installed 277V PHOTOCELL