



Wall Pack AWP13 H: 13 W: 7.75 E: 5.50

Description

Mini die cast Wall Pack supplied with fully gasketted borosilicate glass diffuser

Specifications

Housing	Die-cast aluminum			
Diffuser/Optics	Prismatic Borosilicate glass			
Light Source	Fluorescent	HID	LED	Fluorescent
Max Watts	42	50	18.6	42 X 2
Electrical	HID - Includes Pulse-start metal halide lamp with 120/277V HPF magnetic ballast			
Mounting	Mounts over 4" recessed outlet box or via surface conduit			
Certification				

Ordering Guide: Choose from each category, using designated code to specify.



Diffuser/Optics

Clear Prismatic Borosilicate glass

Light Source

- L19 LTE 50K - 18.6W/50K 2610 lumen LED
- 2F26 TE - 52W/30K 3600 lumen CF
- F26 TE - 26W/30K 1800 lumen CF
- F32 TE - 32W/30K 2400 lumen CF
- 2F32 TE - 64W/30K 4800 lumen CF
- 2F42 TE - 84W/30K 6400 lumen CF
- F42 TE - 42W/30K 3200 lumen CF
- M50 DT - 50W PSMH 120/277V HPF

Finish

- Standard
- ZT - Bronze

Extras (Order Separately)

- BBE Battery Backup - For Compact Fluorescent only (specify 120V Or 277V)
- PC1 Field installed 120V PHOTOCELL
- PC2 Field installed 277V PHOTOCELL