



Wall Pack AWP13 H: 13 W: 7.75 E: 5.50

Description

Mini die cast Wall Pack supplied with fully gasketted borosilicate glass diffuser

Specifications

| | | | | |
|---------------|---|-----|------|-------------|
| Housing | Die-cast aluminum | | | |
| Diffuser | Prismatic Borosilicate glass | | | |
| Light Source | Fluorescent | HID | LED | Fluorescent |
| Max Watts | 42 | 50 | 18.6 | 42 X 2 |
| Electrical | HID - Includes Pulse-start metal halide lamp with 120/277V HPF magnetic ballast | | | |
| Mounting | Mounts over 4" recessed outlet box or via surface conduit | | | |
| Certification | | | | |

Ordering Information Choose one from each category, filling in the guide using designated code.

| | | | | | |
|-------|--------------|-------------|--------------|-------------|-------------|
| Guide | <u>AWP13</u> | <u> </u> | <u> </u> | <u> </u> | <u> </u> |
| | MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |

| | | | |
|---|--|--|---|
| Diffuser Clear Prismatic Borosilicate glass | Light Source L19 LTE 50K - 18.6W/50K 2610 lumen LED 2F26 TE - 52W/30K 3600 lumen CF F26 TE - 26W/30K 1800 lumen CF F32 TE - 32W/30K 2400 lumen CF 2F32 TE - 64W/30K 4800 lumen CF 2F42 TE - 84W/30K 6400 lumen CF F42 TE - 42W/30K 3200 lumen CF M50 DT - 50W PSMH 120/277V HPF | Finish Standard ZT - Bronze | Extras (Order Separately) BBE Battery Backup - For Compact Fluorescent only (specify 120V Or 277V) PC1 Field installed 120V PHOTOCELL PC2 Field installed 277V PHOTOCELL |
|---|--|--|---|