



Wall Pack AWP14 H: 11 W: 5.25 E: 6.75

Description

Mini Hooded Polycarbonate Wall Pack supplied with fully gasketted clear prismatic polycarbonate diffuser and anodized aluminum reflector

Specifications

Housing	Die-cast aluminum	
Diffuser/Optics	Polycarbonate Prismatic Lens	
Light Source	Fluorescent	LED
Max Watts	42	13
Electrical	LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver. QE/TE - Includes 4-pin CF lamp with 120-277V HPF electronic ballast	
Mounting	Mounts over 4" recessed outlet box or via surface conduit	
Certification		



Ordering Guide: Choose from each category, using designated code to specify.

AWP14					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

Polycarbonate Prismatic Lens

Light Source

L13 LTE 50K - 12.5W/50K 1658 lumen LED
F26 TE - 26W/30K 1800 lumen CF
F32 TE - 32W/30K 2400 lumen CF
F42 TE - 42W/30K 3200 lumen CF

Finish

Standard
ZT - Bronze

Extras (Order Separately)

PC1 Field installed 120V PHOTOCELL
PC2 Field installed 277V PHOTOCELL