



Wall Pack AWP15 H: 9 W: 14.25 E: 7.25

Description

Medium Wall Pack

Specifications

Housing	Die-cast aluminum w/Hinged front frame			
Diffuser	Prismatic Borosilicate glass			
Light Source	Fluorescent	HID	LED	Fluorescent
Max Watts	42	50	42	42 X 2
Electrical	HID - Includes Pulse-start metal halide lamp with 120/277V HPF magnetic ballast			
Mounting	Mounts over 4" recessed outlet box or via surface conduit			
Certification				

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	<u>AWP15</u>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser
Clear Prismatic Borosilicate glass

Light Source
F26 TE - 26W/30K 1800 lumen CF
2F26 TE - 52W/30K 3600 lumen CF
F32 TE - 32W/30K 2400 lumen CF
2F32 TE - 64W/30K 4800 lumen CF
2F42 TE - 84W/30K 6400 lumen CF
F42 TE - 42W/30K 3200 lumen CF
L42 LTE 50K - 41.5W/50K 5788 lumen LED
M50 DT - 50W PSMH 120/277V HPF

Finish
Standard
ZT - Bronze

Extras (Order Separately)
BBE Battery Backup - For Compact Fluorescent only (specify 120V Or 277V)
PC1 Field installed 120V PHOTOCELL