



## Wall Pack AWP15 H: 9 W: 14.25 E: 7.25

### Description

Medium Wall Pack

### Specifications

Housing	Die-cast aluminum w/Hinged front frame			
Diffuser/Optics	Prismatic Borosilicate glass			
Light Source	Fluorescent	HID	LED	Fluorescent
Max Watts	42	50	42	42 X 2
Electrical	HID - Includes Pulse-start metal halide lamp with 120/277V HPF magnetic ballast			
Mounting	Mounts over 4" recessed outlet box or via surface conduit			
Certification				

**Ordering Guide:** Choose from each category, using designated code to specify.

AWP15					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

#### Diffuser/Optics

Clear Prismatic Borosilicate glass

#### Light Source

- F26 TE - 26W/30K 1800 lumen CF
- 2F26 TE - 52W/30K 3600 lumen CF
- F32 TE - 32W/30K 2400 lumen CF
- 2F32 TE - 64W/30K 4800 lumen CF
- 2F42 TE - 84W/30K 6400 lumen CF
- F42 TE - 42W/30K 3200 lumen CF
- L42 LTE 50K - 41.5W/50K 5788 lumen LED
- M50 DT - 50W PSMH 120/277V HPF

#### Finish

- Standard**
- ZT - Bronze

#### Extras (Order Separately)

- BBE** Battery Backup - For Compact Fluorescent only (specify 120V Or 277V)
- PC1** Field installed 120V PHOTOCELL