



**Wall Pack AWP15** H: 9 W: 14.25 E: 7.25

**Description**

Medium Wall Pack

**Specifications**

<b>Housing</b>	Die-cast aluminum w/Hinged front frame			
<b>Diffuser/Optics</b>	Prismatic Borosilicate glass			
<b>Light Source</b>	Fluorescent	HID	LED	Fluorescent
<b>Max Watts</b>	42	50	42	42 X 2
<b>Electrical</b>	HID - Includes Pulse-start metal halide lamp with 120/277V HPF magnetic ballast			
<b>Mounting</b>	Mounts over 4" recessed outlet box or via surface conduit			
<b>Certification</b>				

**Ordering Guide:** Choose from each category, using designated code to specify.

AWP15					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

Clear Prismatic Borosilicate glass

**Light Source**

- F26 TE** - 26W/30K 1800 lumen CF
- 2F26 TE** - 52W/30K 3600 lumen CF
- F32 TE** - 32W/30K 2400 lumen CF
- 2F32 TE** - 64W/30K 4800 lumen CF
- 2F42 TE** - 84W/30K 6400 lumen CF
- F42 TE** - 42W/30K 3200 lumen CF
- L42 LTE 50K** - 41.5W/50K 5788 lumen LED
- M50 DT** - 50W PSMH 120/277V HPF

**Finish**

- Standard**
- ZT** - Bronze

**Extras (Order Separately)**

- BBE** Battery Backup - For Compact Fluorescent only (specify 120V Or 277V)
- BBL** 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)
- PC1** Field installed 120V PHOTOCCELL