



Wall Pack/Floodlight AWP15 H: 9 W: 14.25 E: 7.25

Description

Medium Wall Pack

Specifications

- Housing** Die-cast aluminum w/Hinged front frame
- Diffuser/Optics** Prismatic Borosilicate glass
- Light Source** LTE
- Max Watts** 42
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box or via surface conduit
- Certification**



Ordering Guide: Choose from each category, using designated code to specify.

AWP15					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

Clear Prismatic Borosilicate glass

Light Source

L42 LTE 50K - 41.5W/50K 5788 lumen LED

Finish

Standard
ZT - Bronze

Extras (Order Separately)

- (D) FUSE** DOUBLE FUSED
- (S) FUSE** SINGLE FUSED
- BBL** 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)
- PC1** Field installed 120V PHOTOCELL
- SSP** 10KV 120-277V Supplemental Surge Protection