



**Wall Pack AWP15** H: 9 W: 14.25 E: 7.25

**Description**

Medium Wall Pack

**Specifications**

Housing	Die-cast aluminum w/Hinged front frame			
Diffuser	Prismatic Borosilicate glass			
Light Source	Fluorescent	HID	LED	Fluorescent
Max Watts	42	50	42	42 X 2
Electrical	HID - Includes Pulse-start metal halide lamp with 120/277V HPF magnetic ballast			
Mounting	Mounts over 4" recessed outlet box or via surface conduit			
Certification				

**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide	<u>AWP15</u>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser**  
Clear Prismatic Borosilicate glass

**Light Source**  
**F26 TE** - 26W/30K 1800 lumen CF  
**2F26 TE** - 52W/30K 3600 lumen CF  
**F32 TE** - 32W/30K 2400 lumen CF  
**2F32 TE** - 64W/30K 4800 lumen CF  
**2F42 TE** - 84W/30K 6400 lumen CF  
**F42 TE** - 42W/30K 3200 lumen CF  
**L42 LTE 50K** - 41.5W/50K 5788 lumen LED  
**M50 DT** - 50W PSMH 120/277V HPF

**Finish**  
**Standard**  
**ZT** - Bronze

**Extras (Order Separately)**  
**BBE** Battery Backup - For Compact Fluorescent only (specify 120V Or 277V)  
**PC1** Field installed 120V PHOTOCELL