



**Wall Pack/Floodlight AWP20** H: 9.38 W: 18.13 E: 9

**Description**

Large die cast Wall Pack supplied with fully gasketted borosilicate glass diffuser and anodized aluminum reflector

**Specifications**

<b>Housing</b>	Die-cast aluminum w/Hinged front frame
<b>Diffuser/Optics</b>	Prismatic Borosilicate glass
<b>Light Source</b>	LTE
<b>Max Watts</b>	58
<b>Electrical</b>	TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
<b>Mounting</b>	Mounts over 4" recessed outlet box or via surface conduit
<b>Certification</b>	

**Ordering Guide:** Choose from each category, using designated code to specify.

AWP20				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

Clear Prismatic Borosilicate glass

**Light Source**

**L58 LTE 50K** - 58W/50K 8025 lumen LED

**Finish**

**Standard**  
**ZT** - Bronze

**Extras (Order Separately)**

**(D) FUSE** DOUBLE FUSED  
**(S) FUSE** SINGLE FUSED  
**BBL** 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)  
**PC1** Field installed 120V PHOTOCELL  
**PC2** Field installed 277V PHOTOCELL  
**SSP** 10KV 120-277V Supplemental Surge Protection