



Wall Pack/Floodlight AWP35 H: 9-1/8 W: 18 E: 7-1/8

Description

Half Round Cut Off Wall Sconce Downlight, Type III distribution

Specifications

- Housing Die-cast aluminum
- Diffuser/Optics Clear Tempered Glass
- Light Source LTE
- Max Watts 47
- Electrical TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting Mounts over 4" recessed outlet box
- Certification



Ordering Guide: Choose from each category, using designated code to specify.

AWP35				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Clear Tempered Glass lens

Light Source

L47 LTE 50K - 46.5W/50K 5445 lumen LED

Finish

Standard
ZT - Bronze (textured)

Extras (Order Separately)

- (D) FUSE** DOUBLE FUSED
- (S) FUSE** SINGLE FUSED
- BBL** 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)
- PC1** Field installed 120V PHOTOCELL
- PC2** Field installed 277V PHOTOCELL
- SSP** 10KV 120-277V Supplemental Surge Protection