



Wall Pack/Floodlight AWP15 H: 12 W: 11.13 E: 7.88

Description

Curved die cast Wall Pack supplied with fully gasketted borosilicate glass diffuser and anodized aluminum reflector

Specifications

Housing	Die-cast aluminum w/hinged front frame
Diffuser/Optics	Clear Prismatic Borosilicate glass
Light Source	LTE
Max Watts	37.2
Electrical	TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
Mounting	Mounts over 4" recessed outlet box or surface conduit
Certification	



Ordering Guide: Choose from each category, using designated code to specify.

AWPA15					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics
Clear Prismatic glass

Light Source
L37 LTE 50K - 37.2W/50K 5045 lumen LED

Finish
Standard
ZT - Bronze

Extras (Order Separately)
(D) FUSE DOUBLE FUSED
(S) FUSE SINGLE FUSED
BBL 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)
PC1 Field installed 120V PHOTOCELL
PC2 Field installed 277V PHOTOCELL
SSP 10KV 120-277V Supplemental Surge Protection