



**Wall Pack** AWPA15 H: 12 W: 11.13 E: 7.88

**Description**

Curved die cast Wall Pack supplied with fully gasketted borosilicate glass diffuser and anodized aluminum reflector

**Specifications**

Housing	Die-cast aluminum w/hinged front frame			
Diffuser/Optics	Clear Prismatic Borosilicate glass			
Light Source	Fluorescent	HID	LED	Fluorescent
Max Watts	42	50	37.2	42 X 2
Mounting	Mounts over 4" recessed outlet box or surface conduit			
Certification				

**Ordering Guide:** Choose from each category, using designated code to specify.

AWPA15					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**  
Clear Prismatic glass

**Light Source**  
**2F26 QE** - 52W/27K 3600 lumen CF  
**F26 TE** - 26W/30K 1800 lumen CF  
**2F32 TE** - 64W/30K 4800 lumen CF  
**F32 TE** - 32W/30K 2400 lumen CF  
**L37 LTE 50K** - 37.2W/50K 5045 lumen LED  
**F42 TE** - 42W/30K 3200 lumen CF  
**2F42 TE** - 84W/30K 6400 lumen CF  
**M50 DT** - 50W PSMH 120/277V HPF

**Finish**  
**Standard**  
**ZT** - Bronze

**Extras (Order Separately)**