



**Wall Pack** **AWPA15** H: 12 W: 11.13 E: 7.88

**Description**

Curved die cast Wall Pack supplied with fully gasketted borosilicate glass diffuser and anodized aluminum reflector

**Specifications**

Housing	Die-cast aluminum w/hinged front frame			
Diffuser	Clear Prismatic Borosilicate glass			
Light Source	Fluorescent	HID	LED	Fluorescent
Max Watts	42	50	37.2	42 X 2
Mounting	Mounts over 4" recessed outlet box or surface conduit			
Certification				

**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide	<u>AWPA15</u>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

<b>Diffuser</b>	<b>Light Source</b>	<b>Finish</b>	<b>Extras (Order Separately)</b>
Clear Prismatic glass	<b>2F26 QE</b> - 52W/27K 3600 lumen CF <b>F26 TE</b> - 26W/30K 1800 lumen CF <b>2F32 TE</b> - 64W/30K 4800 lumen CF <b>F32 TE</b> - 32W/30K 2400 lumen CF <b>L37 LTE 50K</b> - 37.2W/50K 5045 lumen LED <b>F42 TE</b> - 42W/30K 3200 lumen CF <b>2F42 TE</b> - 84W/30K 6400 lumen CF <b>M50 DT</b> - 50W PSMH 120/277V HPF	<b>Standard</b> <b>ZT</b> - Bronze	