



Wall Pack AWPA15 H: 12 W: 11.13 E: 7.88

Description

Curved die cast Wall Pack supplied with fully gasketted borosilicate glass diffuser and anodized aluminum reflector

Specifications

Housing	Die-cast aluminum w/hinged front frame			
Diffuser/Optics	Clear Prismatic Borosilicate glass			
Light Source	Fluorescent	HID	LED	Fluorescent
Max Watts	42	50	37.2	42 X 2
Mounting	Mounts over 4" recessed outlet box or surface conduit			
Certification				

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	<u>AWPA15</u>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Clear Prismatic glass

Light Source

- 2F26 QE - 52W/27K 3600 lumen CF
- F26 TE - 26W/30K 1800 lumen CF
- 2F32 TE - 64W/30K 4800 lumen CF
- F32 TE - 32W/30K 2400 lumen CF
- L37 LTE 50K - 37.2W/50K 5045 lumen LED
- F42 TE - 42W/30K 3200 lumen CF
- 2F42 TE - 84W/30K 6400 lumen CF
- M50 DT - 50W PSMH 120/277V HPF

Finish

- Standard**
- ZT - Bronze

Extras (Order Separately)