



Wall Pack AWPB40 H: 12.25 W: 10.38 E: 7.38

Description

Euro styled Polycarbonate Hooded Wall Pack supplied with fully gasketted clear prismatic polycarbonate diffuser and anodized aluminum reflector

Specifications

Housing	Die-cast aluminum with polycarbonate front		
Diffuser	Clear Ribbed Polycarbonate		
Light Source	Fluorescent	LED	Fluorescent
Max Watts	42	33.5	42 X 2
Mounting	Mounts over 4" recessed outlet box or surface conduit		
Certification			

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide AWPB40

MODEL DIFFUSER LIGHT SOURCE FINISH EXTRAS

Diffuser
Ribbed Polycarbonate

Light Source
2F26 QE - 52W/27K 3600 lumen CF
F26 TE - 26W/30K 1800 lumen CF
2F32 TE - 64W/30K 4800 lumen CF
F32 TE - 32W/30K 2400 lumen CF
L34 LTE 50K - 33.5W/50K 4438 lumen LED
F42 TE - 42W/30K 3200 lumen CF
2F42 TE - 84W/30K 6400 lumen CF

Finish
Standard
ZT - Bronze

Extras (Order Separately)
BBE Battery Backup - For Compact Fluorescent only (specify 120V Or 277V)