



Wall Pack AWPB40 H: 12.25 W: 10.38 E: 9.38

Description

Euro styled Polycarbonate Hooded Wall Pack supplied with fully gasketted clear prismatic polycarbonate diffuser and anodized aluminum reflector

Specifications

Housing	Die-cast aluminum with polycarbonate front		
Diffuser/Optics	Clear Ribbed Polycarbonate		
Light Source	Fluorescent	LED	Fluorescent
Max Watts	42	33.5	42 X 2
Electrical	LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver. QE/TE - Includes 4-pin CF lamp with 120-277V HPF electronic ballast		
Mounting	Mounts over 4" recessed outlet box or surface conduit		
Certification			



Ordering Guide: Choose from each category, using designated code to specify.

AWPB40					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics
Ribbed Polycarbonate

Light Source
F26 TE - 26W/30K 1800 lumen CF
2F26 TE - 52W/30K 3600 lumen CF
F32 TE - 32W/30K 2400 lumen CF
2F32 TE - 64W/30K 4800 lumen CF
L34 LTE 50K - 33.5W/50K 4438 lumen LED
2F42 TE - 84W/30K 6400 lumen CF
F42 TE - 42W/30K 3200 lumen CF

Finish
Standard
ZT - Bronze

Extras (Order Separately)
(D) FUSE DOUBLE FUSED
(S) FUSE SINGLE FUSED
BBE Battery Backup - For Compact Fluorescent only (specify 120V Or 277V)
SSP 10KV 120-277V Supplemental Surge Protection