



Project: _____

Fixture Type: _____



Wall Pack/Floodlight AWPB40

H: 12.25 W: 10.38 E: 9.38

Description

Euro styled Polycarbonate Hooded Wall Pack supplied with fully gasketted clear prismatic polycarbonate diffuser and anodized aluminum reflector

Specifications

- Housing** Die-cast aluminum with polycarbonate front
- Diffuser/Optics** Clear Ribbed Polycarbonate
- Light Source** LTE
- Max Watts** 33.5
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box or surface conduit
- Certification**



Ordering Guide: Choose from each category, using designated code to specify.

AWPB40					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

Ribbed Polycarbonate

Light Source

L34 LTE 50K - 33.5W/50K 4438 lumen LED

Finish

Standard
ZT - Bronze

Extras (Order Separately)

- (D) FUSE** DOUBLE FUSED
- (S) FUSE** SINGLE FUSED
- PC1** Field installed 120V PHOTOCELL
- PC2** Field installed 277V PHOTOCELL
- SSP** 10KV 120-277V Supplemental Surge Protection