



Wall Pack AWPB40 H: 12.25 W: 10.38 E: 7.38

Description

Euro styled Polycarbonate Hooded Wall Pack supplied with fully gasketted clear prismatic polycarbonate diffuser and anodized aluminum reflector

Specifications

Housing	Die-cast aluminum with polycarbonate front		
Diffuser/Optics	Clear Ribbed Polycarbonate		
Light Source	Fluorescent	LED	Fluorescent
Max Watts	42	33.5	42 X 2
Mounting	Mounts over 4" recessed outlet box or surface conduit		
Certification			

Ordering Guide: Choose from each category, using designated code to specify.



Diffuser/Optics

Ribbed Polycarbonate

Light Source

- 2F26 QE** - 52W/27K 3600 lumen CF
- F26 TE** - 26W/30K 1800 lumen CF
- 2F32 TE** - 64W/30K 4800 lumen CF
- F32 TE** - 32W/30K 2400 lumen CF
- L34 LTE 50K** - 33.5W/50K 4438 lumen LED
- F42 TE** - 42W/30K 3200 lumen CF
- 2F42 TE** - 84W/30K 6400 lumen CF

Finish

- Standard**
- ZT** - Bronze

Extras (Order Separately)

- BBE** Battery Backup - For Compact Fluorescent only (specify 120V Or 277V)