



Wall Pack AWPC15 H: 9-1/8 W: 14.25 E: 11.38

Description

Full-Cutoff Wall Pack

Specifications

Housing	Die-cast aluminum		
Diffuser/Optics	Clear Tempered Glass		
Light Source	Fluorescent	LED	Fluorescent
Max Watts	42	37.2	42 X 2
Mounting	Mounts over 4" recessed outlet box		
Certification	Manufactured in accordance with U.L. standard 1598 -		

Ordering Guide: Choose from each category, using designated code to specify.

AWPC15				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Clear Tempered Glass

Light Source

- 2F26 QE** - 52W/27K 3600 lumen CF
- F26 TE** - 26W/30K 1800 lumen CF
- 2F32 TE** - 64W/30K 4800 lumen CF
- F32 TE** - 32W/30K 2400 lumen CF
- L37 LTE 50K** - 37.2W/50K 4764 lumen LED
- F42 TE** - 42W/30K 3200 lumen CF
- 2F42 TE** - 84W/30K 6400 lumen CF

Finish

- Standard**
- ZT** - Bronze

Extras (Order Separately)

- BBE** Battery Backup - For Compact Fluorescent only (specify 120V Or 277V)