



Cutoff/Downlight AWPC15 H: 9-1/8 W: 14.25 E: 11.38

Description

Full-Cutoff Wall Pack

Specifications

Housing	Die-cast aluminum		
Diffuser	Clear Tempered Glass		
Light Source	Fluorescent	LED	Fluorescent
Max Watts	42	37.2	42 X 2
Mounting	Mounts over 4" recessed outlet box		
Certification	Manufactured in accordance with U.L. standard 1598 -		
Applications	Floodlights & Wall Packs		

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide AWPC15

MODEL DIFFUSER LIGHT SOURCE FINISH EXTRAS

Diffuser
Clear Tempered Glass

Light Source
2F26 QE - 52W/27K 3600 lumen CF
F26 TE - 26W/30K 1800 lumen CF
2F32 TE - 64W/30K 4800 lumen CF
F32 TE - 32W/30K 2400 lumen CF
L37 LTE 50K - 37.2W/50K 4764 lumen LED
F42 TE - 42W/30K 3200 lumen CF
2F42 TE - 84W/30K 6400 lumen CF

Finish
Standard
ZT - Bronze

Extras (Order Separately)
BBE Battery Backup - For Compact Fluorescent only (specify 120V Or 277V)