



Wall Pack/Floodlight AWPC15 H: 9-1/8 W: 14.25 E: 11.38

Description

Full-Cutoff Wall Pack

Specifications

- Housing** Die-cast aluminum
- Diffuser/Optics** Clear Tempered Glass
- Light Source** LTE
- Max Watts** 37.2
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box
- Certification** Manufactured in accordance with U.L. standard 1598 -



Ordering Guide: Choose from each category, using designated code to specify.

AWPC15				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Clear Tempered Glass

Light Source

L37 LTE 50K - 37.2W/50K 4764 lumen LED

Finish

Standard
ZT - Bronze

Extras (Order Separately)

(D) FUSE DOUBLE FUSED
(S) FUSE SINGLE FUSED
BBL 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)
SSP 10KV 120-277V Supplemental Surge Protection