



**Cutoff/Downlight AWPC15** H: 9-1/8 W: 14.25 E: 11.38

**Description**

Full-Cutoff Wall Pack

**Specifications**

Housing	Die-cast aluminum		
Diffuser	Clear Tempered Glass		
Light Source	Fluorescent	LED	Fluorescent
Max Watts	42	37.2	42 X 2
Mounting	Mounts over 4" recessed outlet box		
Certification	Manufactured in accordance with U.L. standard 1598 -		

**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide	<u>AWPC15</u>	<u>    </u>	<u>    </u>	<u>    </u>	<u>    </u>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

<p><b>Diffuser</b></p> <p>Clear Tempered Glass</p>	<p><b>Light Source</b></p> <p><b>2F26 QE</b> - 52W/27K 3600 lumen CF  <b>F26 TE</b> - 26W/30K 1800 lumen CF  <b>2F32 TE</b> - 64W/30K 4800 lumen CF  <b>F32 TE</b> - 32W/30K 2400 lumen CF  <b>L37 LTE 50K</b> - 37.2W/50K 4764 lumen LED  <b>F42 TE</b> - 42W/30K 3200 lumen CF  <b>2F42 TE</b> - 84W/30K 6400 lumen CF</p>	<p><b>Finish</b></p> <p><b>Standard</b>  <b>ZT</b> - Bronze</p>	<p><b>Extras (Order Separately)</b></p> <p><b>BBE</b> Battery Backup - For Compact Fluorescent only (specify 120V Or 277V)</p>
--	--	---	--