



**Bulkhead** **AWPR22OF** W: 14.50 E: 5.75

**Description**

14-1/2" Round Open Frame Bulkhead

**Specifications**

- Housing Die-cast aluminum
- Diffuser Opalescent polycarbonate
- Light Source Fluorescent
- Max Watts 42 X 2
- Electrical QE/TE - Includes 4-pin CF lamp with 120-277V HPF electronic ballast
- Mounting Surface mount, or conduit entry via two 1/2" knockouts
- Certification

**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide AWPR22OF

MODEL                      DIFFUSER                      LIGHT SOURCE                      FINISH                      EXTRAS

- |  |  |   |   |
|--|--|---|---|
| <p><b>Diffuser</b></p> <p>Opalescent (white) polycarbonate</p> | <p><b>Light Source</b></p> <p><b>2F26 TE</b> - 52W/30K 3600 lumen CF<br/> <b>2F32 TE</b> - 64W/30K 4800 lumen CF<br/> <b>2F42 TE</b> - 84W/30K 6400 lumen CF</p> | <p><b>Finish</b></p> <p><b>Standard</b><br/> <b>WT</b> - White (textured)<br/> <b>ZT</b> - Bronze</p> | <p><b>Extras (Order Separately)</b></p> |
|--|--|---|---|

NOTES: Wall Mount ONLY